



MATERIAL SAFETY DATA SHEET (MSDS)

Baseboard Stripper

Aerosol Baseboard Stripper

Specialty Cleaners



SECTION I ► PRODUCT IDENTIFICATION					
Product Name		Product Type		WHMIS Classification	
Baseboard Stripper		Aerosol Baseboard Stripper		A, D1A, D2B, E	
SECTION II ► HAZARDOUS INGREDIENTS					
Chemical Name		Cas Registry No.	%	Toxicity	
Sodium Metasilicate		10213-79-3	1-5	LD50 ORAL (RAT) 1153 mg/kg	
Ethylene Glycol Monobutyl Ether		111-76-2	1-5	LD50 ORAL (RAT) 530-2616 mg/kg	
Propane		74-98-6	0.1-1.0	LD50 DERMAL (RABBITS) >5000 mg/kg	
Isobutane		75-28-5	1-5	Not Available	
SECTION III ► PHYSICAL DATA					
Appearance	Odour	pH	Boiling Point	Specific Gravity	Solubility in Water
Cloudy, white	Fragrant	10.4-10.8	100-175 °C	0.92-0.96 (aerosol), 0.96-1.00 (liquid)	100%
SECTION IV ► FIRE AND EXPLOSION HAZARD DATA					
Flash Point (°C): 60			Extinguishing media: Water, carbon dioxide, dry chemical, foam.		
Special fire fighting procedures: Use water fog to keep container cool and prevent build-up if exposed to extreme temperature. Full protective equipment including self contained breathing apparatus should be worn in a fire involving this material.					
Unusual fire and explosion hazards: Contents under pressure. Container may explode if heated.					
SECTION V ► TOXICOLOGICAL PROPERTIES					
HAZARD RATING: Health = 2 Flammability = 1 Reactivity = 0					Rating System 0 = Insignificant 1 = Slight 2 = Moderate 3 = High 4 = Extreme
Swallowing: May cause red blood cell hemolysis and possible liver and kidney damage. May cause headache, nausea, vomiting and weakness.					
Inhalation: : May cause irritation. Propellant is a simple asphyxiant.					
Skin Absorption: Can penetrate skin readily. Frequent or wide spread contact may result in similar results as "ingestion".					
Skin Contact: : May cause irritation.					
Eye Contact: Causes moderate irritation and possibly corneal injury.					
Special Warning: None					
SECTION VI ► FIRST AID MEASURES					
Ingestion: Do not induce vomiting. Call a physician immediately.					
Inhalation: Remove to fresh air.					
Skin: Wash thoroughly with soap and water.					
Eyes: Flush with plenty of water for least 15 minutes. Call a physician immediately.					
SECTION VII ► REACTIVITY DATA					
Stable: Yes					
Conditions to avoid: Temperatures above 50°C, excessive heat, sparks and open flames.					
Incompatibility with other materials: Strong oxidizing agents.					
Hazardous decomposition products: Hydrocarbon fumes and smoke. Carbon monoxide where combustion is incomplete.					
Hazardous polymerization: Will not occur.					
SECTION VIII ► PREVENTIVE MEASURES					
Hand protection: Wear chemical resistant gloves.					
Eye protection: Safety glasses.					
Ventilation: General					
Respiratory protection: If used indoors on a continuous basis, use of a cartridge type respirator is recommended.					
Other protective equipment: None					
Steps to be taken in case material is released or spilled: Remove all sources of ignition. Use an inert absorbent material and remove non-sparking tools. Ventilate area. Prevent from entering a watercourse.					
Waste disposal method: Do not puncture or incinerate even if empty. Use standard waste disposal methods in accordance with municipal, provincial and federal regulations.					
Precautions to be taken in handling and storage: Store in a cool, well ventilated area below 50°C. Keep away from heat, sparks and open flames.					
Other precautions: Follow label use instructions.					
UN: 1950		TDG Class: 2.1 (Ltd. Qty.)		Packing Group: Not Applicable	
TDG Emergency Telephone Number: 613-996-6666 (COLLECT)					
SECTION IX ► PREPARATION DATA					
Prepared by: M. Mikoluk			Last updated: August 24th, 2016		
Location: Dustbane Products Limited, 25 Pickering Place, Ottawa, Ontario, K1G 5P4 – 613-745-6861					

Baseboard Stripper

Aerosol Baseboard Stripper

“Excellent foam cleaner which clings to vertical surfaces to remove floor finish and soil build-up.”

FEATURES AND BENEFITS

Heavy duty stripper: Removes wax and copolymer floor finishes.

Convenient packaging: Fast, effective and easy to use.

Does not contain C.F.C.: Does not affect the ozone layer.

WHERE TO USE

For baseboards, floors, corners, tiles and porcelain.

HOW TO USE

Shake well before use. Wear gloves. Hold can upright 15-25 cm from surface to be sprayed. Apply a thin even coat and wait 3-5 minutes. Wipe all residues off surfaces with a wet sponge. For stubborn film, rub with a wet scrub pad or sponge. Be sure to remove any overspray as soon as possible.

SPECIFICATIONS

Appearance: Cloudy, white

Fragrance : Fragrant

WHMIS : Yes

TDG : Yes