



#### **Applications:**

Preparation:

Before your initial application, the floor must be stripped of any old finish, rinsed thoroughly with potable water and allowed to dry.

Application:Using a clean mop or sprayer, apply 2-3 coats (depending on the porosity of the floor) allowing the floor<br/>to completely dry between coats, at least 30-60 minutes or more depending on humidity condition.

## **Benefits:**

- Ideal as a base coat for floor finishes
- The solids fill and seal pores as they harden
- Provides a smoother floor surface
- Excellent slip resistance
- Detergent resistant
- High durability for long-lasting protection
- Protects both resilient and non-resilient floors

## Codes:

Product Codes:	53784 (5 L) 53785 (20 L)
• UPC:	0 56069 53784 1 (5 L) 0 56069 53785 8 (20 L)



# **Specifications:**

Colour	White
DIN	No
Odour	Acrylic
рН	8.4 - 8.8
Viscosity	Not determined
Solvent	No
Phosphates	No
WHMIS	Yes
ECOLOGO	No
Food Safe	No
Kosher	Yes
Shelf Life	Up to 3 years after manufacturing
Coverage	170 m <sup>2</sup> (1830 ft <sup>2</sup> ) to 280 m <sup>2</sup> (3014 ft <sup>2</sup> ) (5 L)
Number of Coats	2 - 3
Drying Time	30 - 60 minutes
Solid Content	20%
COF	0.7
Shelf Life	Up to 3 years after manufacturing

**Available Formats:** 



#### Packaging:

Bottle:	6.1" x 6.1" x 12.6" (15.5 x 15.5 x 31.9 cm) 12.25 lbs (5.56 kg)
Pail:	12" x 12" x 16" (30.5 x 30.5 x 41 cm) 48 lbs (22 kg)
Box:	12.4" x 12.4" x 13" 49 lbs (22.23 kg) 4 per case