

# Elite

## All Systems Floor Finish



### Applications:

#### Preparation:

Before your initial application, the floor must be stripped of any old finish, rinsed thoroughly with potable water and allowed to dry. Sealing the floor is recommended prior to applying a floor finish.

#### Application:

Using a clean mop and bucket, apply 1-3 coats (depending on the porosity of the floor) allowing the floor to completely dry between coats, at least 30 minutes or more.

#### Maintenance:

Sweep or dry mop frequently. Wet mop or auto-scrub periodically with a properly diluted neutral detergent. Scrub and recoat worn traffic areas as required. Spray buff as needed. Burnishing daily is highly recommended but not imperative.

### Benefits:

- Exceptional gloss
- Wear and scuff resistant
- Excellent slip resistance
- Detergent resistant
- Protects both resilient and non-resilient floors


### Codes:

- **Product codes:** 52051 (5 L)  
52052 (20 L)
- **UPC:** 0 56069 52051 5 (5 L)  
0 56069 52052 2 (20 L)

### Specifications:

Colour	White
DIN	No
Odour	Acrylic
pH	8.2 - 8.7
Viscosity	Not determined
Solvent	No
Phosphates	No
WHMIS	Yes
ECOLOGO	No
Food Safe	No
Kosher	Yes
Coverage	170 m <sup>2</sup> (1830 ft <sup>2</sup> ) to 280 m <sup>2</sup> (3014 ft <sup>2</sup> ) (5 L)
Number of Coats	1 - 3
Drying Time	30 minutes
Refractive Index	27.3 - 27.9
Non-Volatile Solids	20%
COF	0.6
Gloss Rating	85 - 89%
Shelf Life	Up to 3 years after manufacturing
# of Cases per pallet	36 (5 L) / 36 pails (20 L)

### Available Formats:



5 L

20 L

### Packaging:

- Bottle:** 6.1" x 6.1" x 12.6" (15.5 x 15.5 x 31.9 cm)  
12.25 lbs (5.56 kg)
- Pail:** 12" x 12" x 16" (30.5 x 30.5 x 41 cm)  
48 lbs (22 kg)
- Box (5 L):** 12.4" x 12.4" x 13"  
49 lbs (22.23 kg)  
4 per case

