

Runway

High Durability Floor Finish



Applications:

Preparation:

Before your initial application, the floor must be stripped of any old finish, rinsed thoroughly with potable water and allowed to dry. Sealing the floor is recommended prior to applying a floor finish.

Application:

Using a clean mop and bucket, apply 1-3 coats (depending on the porosity of the floor) allowing the floor to dry completely between coats, at least 30 minutes or more.

Maintenance:

Maintain by dust and/or wet mop daily and choosing the maintenance system which suits your needs.

Benefits:

- Exceptional gloss
- Wear and scuff resistant
- Excellent slip resistance
- Detergent resistant
- Protects both resilient and non-resilient floors

Codes:

- **Product codes:** 52163 (4 L)
52164 (20 L)
- **UPC:** 0 56069 52163 5 (4 L)
0 56069 52164 2 (20 L)

Specifications:

Colour	White
DIN	No
Odour	Acrylic
pH	8.2 - 8.8
Viscosity	Not determined
Solvent	No
Phosphates	No
WHMIS	Yes
ECOLOGO	No
Food Safe	No
Kosher	Yes
Coverage	137 m ² (1480 ft ²) to 224 m ² (2410 ft ²) (4 L)
Number of Coats	1 - 3
Drying Time	30 minutes
Refractive Index	31.7 - 32.1
Non-Volatile Solids	25%
COF	0.5
Gloss Rating	89 - 92%
Shelf Life	Up to 3 years after manufacturing



Available Formats:



4 L



20 L

Packaging:

Bottle: 5.8" x 5.8" x 12.3" (14.7 x 14.7 x 31 cm)
10 lbs (4.5 kg)

Pail: 12" x 12" x 16" (30.5 x 30.5 x 41 cm)
48 lbs (22 kg)

Box (4 L): 11.6" x 11.6" x 12.9"
40 lbs (18 kg)
4 per case